CORRECTED VERSION

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 10 September 1999 (10.09.1999)

(72) Inventors; and

(US).

19482-0980 (US).

(10) International Publication Number WO 99/44535 A1

(75) Inventors/Applicants (for US only): TSENG, David [CN/US]; 8 Baron Park Lane #14, Burlington, MA 01803

(74) Agents: PRESTIA, Paul, F. et al.; Ratner & Prestia, 301

(US). GOLDS, Ellen [US/US]; 32 South Drive, Hastings-on-Hudson, NY 10706 (US). PARSONS, Bruce

[US/US]; 260 S.W. 18th Port, Pompano Beach, FL 33060

One Westlakes (Berwyn), P.O. Box 980, Valley Forge, PA

- (51) International Patent Classification6: 2/06, A61M 29/00
- A61F 2/04,
- (21) International Application Number: PCT/US99/04694
- (22) International Filing Date: 4 March 1999 (04.03.1999)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


60/076,946

5 March 1998 (05.03.1998) US

- (81) Designated States (national): AU, CA, JP, US.
- (71) Applicant (for all designated States except US): BOSTON SCIENTIFIC LIMITED [US/BB]; The Corporate Center, Bush Hill, Bay Street, St. Michael (BB).
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

[Continued on next page]

(54) Title: INTRALUMINAL STENT



(57) Abstract: This invention is an intraluminal stent (10) made of a zigzag or sinusoidal member defining a successive series of struts (14) connected by apex sections (15), and formed into a series of axially displaced hoop members (12a-12n) wherein at least one of the hoop members has at least one strut (14) connected to a strut (14) of an adjacent hoop. The connected struts (14) may be connected by spot welding, continuous welding, or suturing, for example, or by a bridging member (26) connected to each strut (14), and may be spaced along the length of the stent in a pattern to form a connective spine (16). The number of zigs of the zigzag member in each hoop member (12a-12n) may be varied, as can the zig length (L1). A plurality of connective spines (16) may also be included.



Published:

with international search report

(48) Date of publication of this corrected version:

1 November 2001

(15) Information about Corrections: see PCT Gazette No. 44/2001 of 1 November 2001, Section II Previous Correction:

see PCT Gazette No. 48/1999 of 2 December 1999, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

CORRECTED VERSION

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 10 September 1999 (10.09.1999)

PCT

(72) Inventors; and

(US).

(10) International Publication Number WO 99/44535 A1

[CN/US]; 8 Baron Park Lane #14, Burlington, MA 01803 (US). GOLDS, Ellen [US/US]; 32 South Drive, Hast-

ings-on-Hudson, NY 10706 (US). PARSONS, Bruce

[US/US]; 260 S.W. 18th Port, Pompano Beach, FL 33060

One Westlakes (Berwyn), P.O. Box 980, Valley Forge, PA

(75) Inventors/Applicants (for US only): TSENG, David

(74) Agents: PRESTIA, Paul, F. et al.; Ratner & Prestia, 301

(51) International Patent Classification⁶: 2/06, A61M 29/00

A61F 2/04,

(21) International Application Number: PCT/US99/04694

(22) International Filing Date: 4 March 1999 (04.03.1999)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/076,946

5 March 1998 (05.03.1998) US

glish


(81) Designated States (national): AU, CA, JP, US.

19482-0980 (US).

(71) Applicant (for all designated States except US): BOSTON SCIENTIFIC LIMITED [US/BB]; The Corporate Center, Bush Hill, Bay Street, St. Michael (BB). (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

[Continued on next page]

(54) Title: INTRALUMINAL STENT



(57) Abstract: This invention is an intraluminal stent (10) made of a zigzag or sinusoidal member defining a successive series of struts (14) connected by apex sections (15), and formed into a series of axially displaced hoop members (12a-12n) wherein at least one of the hoop members has at least one strut (14) connected to a strut (14) of an adjacent hoop. The connected struts (14) may be connected by spot welding, continuous welding, or suturing, for example, or by a bridging member (26) connected to each strut (14), and may be spaced along the length of the stent in a pattern to form a connective spine (16). The number of zigs of the zigzag member in each hoop member (12a-12n) may be varied, as can the zig length (L1). A plurality of connective spines (16) may also be included.

WO 99/44535 AJ

WO 99/44535 A1



Published:

- with international search report
- (48) Date of publication of this corrected version:

1 November 2001

(15) Information about Corrections: see PCT Gazette No. 44/2001 of 1 November 2001, Section II Previous Correction:

see PCT Gazette No. 48/1999 of 2 December 1999, Section Π

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.